MenuCase





Outdoor Illuminated Menu Case

Product Codes MC-IL-A2-CCT-BL / MC-IL-A2-CCT-BR MC-IL-A3-CCT-BL / MC-IL-A3-CCT-BR MC-IL-A4-CCT-BL / MC-IL-A4-CCT-BR

Introducing the Outdoor Illuminated Menu Case, the perfect solution for showcasing menus, posters, and advertisements. Available in Black and Brass finishes and three sizes (A2, A3, and A4), this sleek backlit menu case features a slim 33mm profile and an internal power supply for easy installation. With an IP65 rating, it's durable for both indoor and outdoor use. The switchable CCT allows you to choose between 6500K and 3000K lighting, ensuring optimal brightness and visibility. Equipped with a lockable design and two keys, this case combines security with style.

IP65 Rated CCT Switchable Lockable Design Slim 33mm Profile Easy Installation 2 Year Warranty*



* Faulty units will be replaced under warranty, providing they are returned.
The warranty does not cover any labour costs involved.
**TradeLED Limited reserve the right to change this information at any time without notice.

Sample photograph, actual product not shown. Result achieved may vary.

SIZES

	9	b	С
A4	310	397	198.5
A3	397	520	260
A2	520	694	347

All sizes are in millimetres.

- Durable Construction
- Contemporary Design
- Easy to use
- 2 Year Warranty*

* Faulty units will be replaced under warranty, providing they are returned.

SPECIFICATION

Product Code	MC-IL-A2-CCT-BL MC-IL-A2-CCT-BR	MC-IL-A3-CCT-BL MC-IL-A3-CCT-BR	MC-IL-A4-CCT-BL MC-IL-A4-CCT-BR	
Frame Colour	Black (BL) Brass (BR)	Black (BL) Brass (BR)	Black (BL) Brass (BR)	
Product Dimensions (mm)	520 × 694 × 33	397 × 520 × 33	310 × 397 × 33	
Viewing Size (mm)	A2 (420 × 594)	A3 (297 × 420)	A4 (210 × 297)	
Graphic Size (mm)	440 × 614	317 × 440	230 × 317	
Graphic Orientation	Portrait			
Graphic Material	PET			
Lockable	Yes – 2 Keys Supplied			
Fixings	4 Screws and 4 Wall Plugs			
LED Colour	6500K and 3000K Switchable			
Total Output Wattage	21.6 W (6500K-10.7 W, 3000K-10.9 W)	16.4 W (6500K - 8.1 W, 3000K - 8.3 W)	11.4 W (6500K – 5.7 W, 3000K –5.7 W)	
LED Type	SMD LED 2835			
Total Light Output	541 Lm (BL) 630 Lm (BR)	413 Lm (BL) 465 Lm (BR)	265 Lm (BL) 285 Lm (BR)	
Energy Efficiency	52 Lm/W (BL) 62 Lm/W (BR)	53 Lm/W (BL) 60.6 Lm/W (BR)	50.4 Lm/W (BL) 53 Lm/W (BR)	
Body Material	Aluminium			
IP Rating	IP65			
Cable Length	1000 mm			
Beam Angle	120°			
LED Life	25000 Hours			
CRI	>80			
Input Voltage	100 – 240 V AC			
Output Voltage	24 V DC			
Frequency	50/60 Hz			
Working Temperature	-20 to 45 °C			
Power Factor	0.48			
Net Weight	6.27 Kg	4.26 Kg	3.08 Kg	
Gross Weight	6.42 Kg	4.36 Kg	3.18 Kg	
Warranty	2 Years			

COLOUR PREVIEW



DETAILS PREVIEW







www.tradeled.co.uk

*TradeLED Limited reserve the right to change this information at any time without notice.

IP65

